SAFETY & SECURITY DRIVING SUPPORT MOBILE IN MADE EAST DOMETIC

REVERSING SYSTEMS

Safely navigate your precious vehicle through winding backstreets or into narrow parking spaces and tight-spots, your PerfectView safety assistant shows you all you need to see to avoid bumps and

scrapes. The ready-to-install set includes all essential components: a brilliant LCD monitor, a watchful camera, plus all cables and mounting accessories. You can easily upgrade it for more safety.



DOMETIC PERFECTVIEW RVS 545

Reversing video system with silver colour camera and 12.7 cm monitor

- Flat, elegant 12.7 cm LCD monitor
- Up to three cameras can be connected
- Automatic recognition of a trailer camera
- Great image quality in all light conditions
- Small colour camera with closed housing for nearly invisible guidance of cable
- Normal or mirrored picture function
- Temperature-controlled heater



DOMETIC PERFECTVIEW RVS 745

Reversing video system with silver colour camera and 17.8 cm monitor

- Flat, elegant 17.8 cm LCD monitor
- Up to three cameras can be connected
- Automatic recognition of a trailer camera
- Great image quality in all light conditions
- Small colour camera with closed housing for nearly invisible guidance of cable
- Normal or mirrored picture function
- Temperature-controlled heater



SAFE
CONNECTION
Lockable plug-in
connectors are
dust and
waterproof



INTUITIVE OPERATION With illuminated keys and day-night switching



ANTI-REFLECTION TECHNOLOGY

Bright, high-contrast display for excellent readability in all light conditions

REVERSING SYSTEMS SPECIFICATIONS					
Product	RVS 545	RVS 745			
Input Voltage (DC)	12 V	12/24 V			
Weight	0.55 kg	0.6 kg			
Ref No.	960000562	960000563			

REVERSING CAMERAS: EXTRA EYES FOR BETTER VISION

Regardless of what you are driving – a motorhome, van or truck – drive with a peace of mind. PerfectView cameras keep a watchful eye on what is happening around your vehicle. There's a perfect model

for every demand: standard or heavy-duty, with one or two eyes, or as a custom fit for tricky mounting conditions. Enjoy clear pictures day and night, on cold winter days and in the summer sun.







DOMETIC PERFECTVIEW CAM18

Colour ball camera

- Real-view or familiar rear mirror picture with 270,000 pixel resolution
- Flexible instalment and alignment, plus freely adjustable ball camera
- Sturdy ABS plastic housing
- Microphone
- Infrared LEDs controlled by light conditions
- Operating temperature –20 °C to +65 °C
- 120° diagonal picture angle

DOMETIC PERFECTVIEW CAM44

Colour twin camera

- Close range wide angle lens 140° diagonal and long range angle lens 50° diagonal view
- Anodised and powder coated aluminium housing with stainless steel cap and mount
- Distance marks (3 lines) in reversing mode
- Microphone
- Manual or automatic switching between the cameras
- 20 m monitor to camera connection cable plus installation fittings for all components
- LRD-controlled infrared LEDs for improved night vision

DOMETIC PERFECTVIEW CAM45

Colour camera, silver, PAL

- Housing with nearly invisible guidance of cable
- Separate infrared LEDs for optimal night-time vision
- Temperature-controlled heater for cold climate use
- Integrated microphone
- Normal or mirrored picture function
- Protection class: IP 69K
- Prepared for connection to navigation systems

REVERSING CAMERA SPECIFICATIONS					
Product	CAM18	CAM44	CAM45		
Dimensions (D x H x W) mm	46 x 83 x 57	65 x 70 x 100	46 x 68 x 80		
Input Voltage (DC)	12 V	12 V	12 V		
Resolution	350000 px	290000 px	250000 px		
Weight	0.82 kg	0.4 kg	0.2 kg		
Ref No.	9102000041	960000043	960000523		

MONITORS: SUPER-FLAT MONITORS WITH BRILLIANT IMAGE QUALITY

Flat, compact and easy to adjust: a PerfectView monitor is the ideal teammate for your reversing camera. You can easily connect more cameras – up to four, depending on the model. The range includes

monitors with 12.7 cm or 17.8 cm screens, all with advanced digital LCD technology to give you high-contrast images day and night. Some models are designed and certified for professional use.





DOMETIC PERFECTVIEW M 55L

Digital 12.7 cm LCD monitor

- Digital LCD technology with LED backlighting achieve top image quality
 day and night
- Flat, compact and easy to adjust thanks to a ball mounting
- Three cameras can be connected for safe all-around vision
- Image settings can be saved separately for each camera input
- Automatic trailer camera recognition
- Elegant monitor base with concealed cable routing
- Mirror function can be set to give you a familiar rear mirror view

DOMETIC PERFECTVIEW M 75L

Digital 17.8 cm LCD monitor

- Digital LCD technology with LED backlighting achieve top image quality
 day and night
- Flat, compact and easy to adjust thanks to a ball mounting
- Three cameras can be connected for safe all-around vision
- Image settings can be saved separately for each camera input
- Automatic trailer camera recognition
- Elegant monitor base with concealed cable routing
- Mirror function can be set to give you a familiar rear mirror view



SAFE
CONNECTION
Lockable plug-in
connectors are
dust- and
waterproof



INTUITIVE OPERATION With illuminated keys and day-night switching



ANTI-REFLECTION TECHNOLOGY

Bright, high-contrast display for excellent readability in all light conditions

MONITORS SPECIFICATIONS			
Product	M 55L	M 75L	
Dimensions (D x H x W) mm	26 x 87 x 148	26 x 110 x 190	
Input Voltage (DC)	12/24 V	12/24 V	
Resolution	384000 px	384000 px	
Weight	0.35 kg	0.4 kg	
Ref No.	960000061	960000062	

CABLE SETS FOR TRAILERS AND TRACTOR-TRAILERS



DOMETIC PERFECTVIEW SYSTEM EXTENSION CABLE 5 M

Extension cable

- Waterproof 6-pin screw connectors
- For light-duty applications
- 5 m extension cable



DOMETIC PERFECTVIEW SYSTEM EXTENSION CABLE 10 M

Extension cable

- Waterproof 6-pin screw connectors
- For light-duty applications
- 10 m extension cable



DOMETIC PERFECTVIEW SYSTEM EXTENSION CABLE 20 M

Standard cable

- Waterproof 6-pin screw connectors
- For light-duty applications
- 20 m extension cable



DOMETIC PERFECTVIEW CAB 38

Quick coupler set including two trailer cables, 30 cm

- Includes surface mounted sockets
- Ready-to-use



DOMETIC PERFECTVIEW ACCESSORIES ADAPT 2

Cable adapter

- Plug and play system upgrading
- No need to lay new cables when replacing older makes of cameras
- 6-pin DIN black cable adapts to Dometic CRT systems built until 2009
- Connects new socket and old plug



DOMETIC PERFECTVIEW ACCESSORIES ADAPT 3

Cable adapter

- Plug and play system upgrading
- No need to lay new cables when replacing older makes of cameras
- 6-pin DIN black cable adapts to Dometic CRT systems built until 2009
- Connects new socket and old plug

REVERSING SYSTEMS ACCESSORIES **SPECIFICATIONS Product** PerfectView system PerfectView system PerfectView system PerfectView CAB 38 PerfectView Adapt 2 PerfectView Adapt 3 extension cable 20 m extension cable 5 m extension cable 10 m 9600000206 9600000207 9600000208 9600000223 9102200043 9102200046 Ref No.

Dometic is a global market leader in branded solutions for mobile living in the areas of Climate, Hygiene & Sanitation and Food & Beverage. Dometic operates in the Americas, EMEA and Asia Pacific, providing products for use in recreational vehicles, trucks and premium cars, pleasure and workboats, and for a variety of other uses. Dometic offer products and solutions that enrich people's experiences away from home, whether in a motorhome, caravan, boat or a truck. Our motivation is to create smart and reliable products with outstanding design. We operate 28 manufacturing/assembly sites in 11 countries, sell our products in approximately 100 countries and manufacture approximately 85% of products sold in-house. We have a global distribution and dealer network in place to serve the aftermarket. Dometic employs approximately 8,200 people worldwide, had net sales of SEK 14.0 billion in 2017 and is headquartered in Solna, Sweden.

E & OE. Please note: Dometic may introduce modifications to products, therefore details herein are subject to change without notice. No liability is accepted for errors. Printing processes may not depict colour accurately.

